

## SAFETY DEVICE

The safety device must be installed at the maximum distance possible from the control mechanism to prevent looped chain becoming slack.

Place the safety device on the wall and mark the positioning of the 2 screw holes.

Drill holes using a suitable drill bit.

Place device into position ensuring the chain is fully taut. Screw into position ensuring device is fully closed.

UNBEATABLE  
**BLINDS**

GREAT BRITISH MADE BLINDS



# Day and Night Blinds Fitting Instructions

## Open Cassette Pelmet

### FACE FIX:



FACE FIX BRACKET

If you have ordered an Open Cassette Pelmet and wish to fit it with face fixing brackets - simply attach the face fix brackets to the wall using appropriate wall plugs and screws then hook the front part of the headrail under the front of the bracket and then gently push on the back of the headrail to secure it in place within the bracket.

### TOP FIX:



TOP FIX BRACKET

If you have ordered an Open Cassette Pelmet and wish to fit it with top fixing brackets - simply attach the top fix brackets using appropriate wall plugs and screws then hook the front part of the headrail under the front of the bracket and then gently push on the back of the headrail to secure it in place within the bracket.

## Matching Fabric Pelmet


### FACE FIX:



FACE FIX BRACKET

If you have ordered a Matching Fabric Pelmet and wish to fit it with face fix brackets - simply attach the face fix brackets to the wall using appropriate screw holes and wall plugs, then gently guide the ends of the headrail into the grooves on the bracket. We will supply you with a middle bracket for extra strength if your blind is over a certain length.

### TOP FIX:



TOP FIX BRACKET

If you have ordered a Matching Fabric Pelmet and wish to fit it with top fixing brackets - simply attach the top fix brackets using appropriate wall plugs and screws then slide the back of the headrail into the bracket until it clicks in place.

**We advise in all cases to test attaching the brackets to the headrail before you fix the brackets into the wall / ceiling.**